

MA1.6s

Light weight, high performance power amplifier

electronics

features

- Switch mode power supply
- Superior sonic performance
- Light weight
- Advanced protection circuits
- Efficient copper cooling system
- Minimum load switches (MLS™)



applications

- Live sound reinforcement
- Fixed installations

The MA1.6s is one of a range of power amplifiers that have been designed to combine reliability and high power with sonic excellence. Utilising an advanced switch mode power supply, the amplifier is characterised by a very high power-to-weight ratio in a lightweight, 2U package. The innovative technology at the heart of the MA1.6s enables it to set new standards in terms of sonic accuracy, impact and clarity.

technical specifications

MAX OUTPUT POWER

EIA AT 1 kHz AND 1% THD

MLS in 0dB position	
8 PER CHANNEL	430 W
4 PER CHANNEL	840 W
2 PER CHANNEL	1200 W
8 BRIDGED	1680 W
4 BRIDGED	2400 W

MAX OUTPUT VOLTAGE

8Ω LOAD	59 Vrms
PEAK VOLTAGE, NO LOAD	85 V

DISTORTION

THD 20Hz – 20kHz AND 1 W TO FULL POWER	0.07%
THD AT 1kHz AND –1dB UNDER CLIP	0.01%
DIM AT –3dB UNDER CLIP	0.008%

HUM AND NOISE

<-105dB	
---------	--

CHANNEL SEPARATION @ 10kHz

70dB	
------	--

OUTPUT IMPEDANCE

30 mΩ	
-------	--

SLEW RATE

60 V/μs	
---------	--

INPUTS

GAIN SELECTABLE (dB)	20, 23, 26, 29, 32, 35, 38, 41
IMPEDANCE	10 kΩ
COMMON MODE REJECTION	50dB

FRONT PANEL

GAIN CONTROLS	31 position detent
---------------	--------------------

INDICATORS: PROTECT	Yellow LED
---------------------	------------

INDICATORS: CLIP	Red LED
------------------	---------

INDICATORS: SIGNAL PRESENT (-40dB)	Green LED
------------------------------------	-----------

REAR PANEL

INPUT CONNECTORS	Neutrik Combo
------------------	---------------

LINK CONNECTOR	XLR-male
----------------	----------

CLIP LIMITERS	On/off each channel
---------------	---------------------

MLS SWITCH	0 or -3dB
------------	-----------

LINK-SWITCH	CH. A-B
-------------	---------

POWER

OPERATION VOLTAGE	130-270V
-------------------	----------

SOFT START	Yes
------------	-----

PEAK INRUSH CURRENT	5 A
---------------------	-----

FULL OUTPUT POWER	180-260 V
-------------------	-----------

MIN START VOLTAGE	175 V
-------------------	-------

115V OPTION	Yes
-------------	-----

CURRENT DRAW AT 4Ω/230V

QUIESCENT POWER (NO LOAD)	1 A rms
---------------------------	---------

1/8 OF FULL POWER (-9dB)	6 A rms
--------------------------	---------

1/3 OF FULL POWER (-5dB)	9 A rms
--------------------------	---------

AT FULL POWER (0dB) @ 1kHz 1%THD	16 A rms
----------------------------------	----------

DIMENSIONS


WIDTH	483mm (19ins)
-------	---------------

HEIGHT	88mm (3.5ins) 2U
--------	------------------

DEPTH (incl. handles)	325mm (12.8ins)
-----------------------	-----------------

WEIGHT	8kg (18lbs)
--------	-------------

overall dimensions



Century Point, Halifax Road, Cressex Business Park,
High Wycombe, Buckinghamshire HP12 3SL, England.
Telephone: +44 (0)1494 535312 Facsimile: +44 (0)1494 438669
E-mail: info@martin-audio.com
All information is Copyright © 2003 Martin Audio Ltd.



www.martin-audio.com